

SMALL BUT MIGHTY!

THE JDM 2 IS OUR CLASSIC MODEL AND IS THE PERFECT SOLUTION FOR MANY DIFFERENT NEEDS!

- 2x3 litre concentrate Bag-in-Box in the device
- 2 drink selection buttons + chilled water
- Preselection Hot or CO₂ – OPTIONAL (model Hot & Cold or CO₂)
- 1 central drink exit with LED lighting (hygienic tempered glass tube), with fully automatic cup sensor
- Automatic cleaning and increased hygiene through airtight seal of concentrates
- Fully electronic control of concentrate dosage and output quantities
- Reliable and made-to-last – premium materials, robust surfaces
- Ease of use – easy refilling, programming, service and cleaning
- Perfect mixing result through patented MidMix®-system
- Multilingual LCD-Info Display (except ECO model)
- Preparation for payment systems + accounting (except ECO model)
- Customized front-display with your own design – OPTIONAL € 36.-



Intelligent central drink dispensing area with LED



Anti-vandalism buttons



2 dispensing heights possible, with low or high drip tray

Available in the following versions:

JDM 2 ECO (with LED bar instead of LCD Display), JDM 2 STILL, JDM 2 CO₂, JDM 2 Hot & Cold, JDM 2 Hot & ambient

TECHNICAL DATA & PRICES

DATA	JDM 2 ECO	JDM 2 STILL	JDM 2 CO ₂	JDM 2 Hot & Cold	JDM 2 Hot & Ambient
Price in € excl. VAT	€	€	€	€	€
Art. Nr.	frucB0200	frucB0201	frucB0202	frucB0203	frucA0204
Width	425 mm	425 mm	425 mm	425 mm	425 mm
Height	435 mm	435 mm	435 mm	435 mm	435 mm
Depth	460 mm	460 mm	460 mm	460 mm	460 mm
Exit height	160 mm - 240 mm	160 mm - 240 mm	160 mm - 240 mm	160 mm - 240 mm	160 mm - 240 mm
Weight	40 kg	40 kg	44 kg	42 kg	28 kg
Preselections	0	0	0	0	0
Product selection buttons (incl. water)	3	3	3	3	3
Automatic caraffe preselection (extra)	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
ESI product labels ²	✓	✓	✓	✓	✓
Flavours	2	2	2	2	2
Mixing ratio concentrates	1+4 ... 1+49*	1+4 ... 1+49	1+4 ... 1+49	1+4 ... 1+49	1+4 ... 1+49
Concentrates in machine	2 x 3lt	2 x 3lt	2 x 3lt	2 x 3lt	2 x 3lt
Dosage of product selection	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS
Cooling capacity	24 l/h	28 l/h	28 l/h	28 l/h	28 l/h
Dispensing temperature	5°C - ambient	5°C - ambient	5°C - ambient	5°C - 90°C	ambient - 90°C
Water pressure in bar	min 1,5 - max 6	min 1,5 - max 6	min 1,5 - max 6	min 1,5 - max 6	min 1,5 - max 6
Voltage	230 V/ 50-60 Hz	230 V/ 50-60 Hz	230 V/ 50-60 Hz	230 V/ 50-60 Hz	230 V/ 50-60 Hz
Power max.	250 W	250 W	320 W	2.700 W	2.400 W
with CO ₂ -carbonator	-	-	✓	-	-
FSS ¹	✓	✓	✓	✓	✓
Flowmeter (water)	✓	✓	✓	✓	✓
Front acrylic glass LED backlight	OPTIONAL	✓	✓	✓	✓
Dispensing area LED light	✓	✓	✓	✓	✓
Coin validator/cashless	-	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
Bookkeeping	-	✓	✓	✓	✓
Payment systems	-	Parallel/EXE	Parallel/EXE	Parallel/EXE	Parallel/EXE
Monitoring Sanitation / Cleaning Interval	-	✓	✓	✓	✓
Syrup Injection Valve (SIV ³)	✓	✓	✓	✓	✓
Automatic cup sensor	-	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
Water gallon + pumpset	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL

ALL our models are equipped with the unique and patented mixing system MidMix II.

1) FSS = Flood security system: avoids water flood problems due to extra safety valve on water entrance.

2) ESI = easy slide in: for fast and easy change of product labels

3) SIV = syrup injection valve for perfect mixing result

*Installation of
water reduction
necessary

SIZE INCL. PACKAGING	JDM 2 ECO	JDM 2 STILL	JDM 2 CO ₂	JDM 2 Hot & Cold	JDM 2 Hot & Ambient
Width	570 mm	570 mm	570 mm	570 mm	570 mm
Height	465 mm	465 mm	465 mm	465 mm	465 mm
Depth	470 mm	470 mm	470 mm	470 mm	470 mm
Weight incl. Packaging	42 kg	42 kg	46 kg	44 kg	30 kg
MACHINE PACKAGE/PALLET					
Europallet 80 x 120 cm	6	6	6	6	6
UK-size pallet 100 x 120 cm	8	8	8	8	8



Save
resources



Save on Warehousing
and Transport



Save
energy



Reduce CO₂
emissions



MADE IN AUSTRIA