

# OUR FLEXIBLE ALL-ROUNDER!

THE JDM 4 ALLOWS MAXIMUM CHOICE AND SERVICE – ALL PACKED IN AN ELEGANT AND COMPACT HOUSING!

- 4x3 litre concentrate Bag-in-Box in the device
- 4 drink selection buttons + chilled water
- Preselection Hot or CO<sub>2</sub> – OPTIONAL (model Hot & Cold or CO<sub>2</sub>)
- 1 central drink exit with LED lighting (hygienic tempered glass tube), with fully automatic cup sensor
- Automatic cleaning and increased hygiene through airtight seal of concentrates
- Fully electronic control of concentrate dosage and output quantities
- Reliable and made-to-last – premium materials, robust surfaces
- Ease of use – easy refilling, programming, service and cleaning
- Perfect mixing result through patented MidMix®-system
- Multilingual LCD-Info Display (except ECO model)
- Preparation for payment systems + accounting (except ECO model)
- Customized front-display with your own design – OPTIONAL € 36.-
- Carafe switch for quick serving by service staff – OPTIONAL



Inner view,  
4 x 3l  
bag-in-box

## Available in the following versions:

JDM 4 ECO (with LED-bar instead of LCD Display),  
JDM 4 STILL, JDM 4 CO<sub>2</sub>, JDM 4 Hot & Cold

Intelligent central  
drink dispensing  
area with LED  
and adjustable  
dispensing height



Anti-  
vandalism  
buttons

# TECHNICAL DATA & PRICES

| DATA                                         | JDM 4 ECO        | JDM 4 STILL      | JDM 4 CO <sub>2</sub> | JDM 4 Hot & Cold |
|----------------------------------------------|------------------|------------------|-----------------------|------------------|
| Price in € excl. VAT                         | €                | €                | €                     | €                |
| Art. Nr.                                     | frucB0400        | frucB0401        | frucB0402             | frucB0403        |
| Width                                        | 425 mm           | 425 mm           | 425 mm                | 425 mm           |
| Height                                       | 650 mm           | 650 mm           | 650 mm                | 650 mm           |
| Depth                                        | 480 mm           | 480 mm           | 480 mm                | 480 mm           |
| Exit height                                  | 160 mm - 280 mm  | 160 mm - 280 mm  | 160 mm - 280 mm       | 160 mm - 280 mm  |
| Weight                                       | 52 kg            | 52 kg            | 56 kg                 | 54 kg            |
| Preselections                                | 0                | 1                | 1                     | 1                |
| Product selection buttons (incl. water)      | 5                | 5                | 5                     | 5                |
| Automatic caraffe preselection (extra)       | OPTIONAL         | OPTIONAL         | OPTIONAL              | OPTIONAL         |
| ESI product labels <sup>2</sup>              | ✓                | ✓                | ✓                     | ✓                |
| Flavours                                     | 4                | 4                | 4                     | 4                |
| Mixing ratio concentrates                    | 1+4 ... 1+49*    | 1+4 ... 1+49     | 1+4 ... 1+49          | 1+4 ... 1+49     |
| Concentrates in machine                      | 4 x 3lt          | 4 x 3lt          | 4 x 3lt               | 4 x 3lt          |
| Dosage of product selection                  | 150-500ml / PULS | 150-500ml / PULS | 150-500ml / PULS      | 150-500ml / PULS |
| Cooling capacity                             | 24 l/h           | 28 l/h           | 28 l/h                | 28 l/h           |
| Dispensing temperature                       | 5°C - ambient    | 5°C - ambient    | 5°C - ambient         | 5°C - 90°C       |
| Water pressure in bar                        | min 1,5 - max 6  | min 1,5 - max 6  | min 1,5 - max 6       | min 1,5 - max 6  |
| Voltage                                      | 230 V/ 50-60 Hz  | 230 V/ 50-60 Hz  | 230 V/ 50-60 Hz       | 230 V/ 50-60 Hz  |
| Power max.                                   | 250 W            | 250 W            | 320 W                 | 2.700 W          |
| with CO <sub>2</sub> -carbonator             | -                | -                | ✓                     | -                |
| FSS <sup>1</sup>                             | ✓                | ✓                | ✓                     | ✓                |
| Flowmeter (water)                            | ✓                | ✓                | ✓                     | ✓                |
| Front acrylic glass LED backlight            | OPTIONAL         | ✓                | ✓                     | ✓                |
| Dispensing area LED light                    | ✓                | ✓                | ✓                     | ✓                |
| Coin validator/cashless                      | -                | OPTIONAL         | OPTIONAL              | OPTIONAL         |
| Bookkeeping                                  | -                | ✓                | ✓                     | ✓                |
| Payment systems                              | -                | Parallel/EXE     | Parallel/EXE          | Parallel/EXE     |
| Monitoring Sanitation /<br>Cleaning Interval | -                | ✓                | ✓                     | ✓                |
| Syrup Injection Valve (SIV <sup>3</sup> )    | ✓                | ✓                | ✓                     | ✓                |
| Automatic cup sensor                         | -                | ✓                | ✓                     | ✓                |
| Water gallon + pumpset                       | OPTIONAL         | OPTIONAL         | OPTIONAL              | OPTIONAL         |

ALL our models are equipped with the unique and patented mixing system MidMix II.

- 1) FSS = Flood security system: avoids water flood problems due to extra safety valve on water entrance.
- 2) ESI = easy slide in: for fast and easy change of product labels
- 3) SIV = syrup injection valve for perfect mixing result

\*Installation of water reduction necessary

| SIZE INCL. PACKAGING        | JDM 4 ECO | JDM 4 STILL | JDM 4 CO <sub>2</sub> | JDM 4 Hot & Cold |
|-----------------------------|-----------|-------------|-----------------------|------------------|
| Width                       | 570 mm    | 570 mm      | 570 mm                | 570 mm           |
| Height                      | 700 mm    | 700 mm      | 700 mm                | 700 mm           |
| Depth                       | 470 mm    | 470 mm      | 470 mm                | 470 mm           |
| Weight incl. Packaging      | 54 kg     | 54 kg       | 58 kg                 | 56 kg            |
| MACHINE PACKAGE/PALLET      |           |             |                       |                  |
| Europallet 80 x 120 cm      | 4         | 4           | 4                     | 4                |
| UK-size pallet 100 x 120 cm | 8         | 8           | 8                     | 8                |

